

# RP-CO2-4B-LAT

## 4 BAR EN-3000 CO2 PRESSURE REGULATOR

Ref. 396.00.704

Fecha: 30/05/2012

Código: FT39600704V0

Revisión: 0

Página: 1/1

### Characteristics

#### Description:

Gas regulation equipment, to secure to cylinder, with regulated gas inlet rod and outlet connection, and two pressure gauges that indicate the gas inlet and outlet pressure from the regulator.

#### APPLICATIONS:

Cylinder gas regulation, to impulse the beer from barrel in catering establishments or mobile outdoor installations.

#### GAS USED:




CO2

#### Main advantages:

- Fine and precise pressure regulation up to 4 bars.
- It prevents exceeding the maximum pressure of 4 bars with mechanical stop. It prevents regulated pressure being handled by the catering user
- Enter key cutting output.



Technical Characteristics	RP-CO2-4B-LAT Ref. 396.00.700
Maximum working pressure (bar)	200 bar
Maximum outlet pressure (bar)	4 bar
Maximum pressure gauge reading (bar)	6 bar
Inlet connection	Ø21,7x14h.RH internal
Outlet connection	1/2"JIC external
Applicable standard for pressure regulator	EN-2503
Applicable standard for pressure gauge	EN-5171
Applicable standard for flexible pigtail	EN-885

assembly-components PD-2R-CO2-LAT				
High gauge		Low gauge		Regulator
	+		+	
Ref. 308.16.225		Ref. 342.16.006		Ref. 396.00.704

**gala gar**  
REGULATION

regulation solutions

INNOVATING • MANUFACTURING • TRAINING • ADVISING